

2.0mm Female Header

Specifications

- ❑ 型態: 180度、90度、SMT
- ❑ 電鍍方式: 鍍金、鍍霧錫、鍍亮錫、鍍錫鉛...(鍍層厚度依客戶要求作調整)
- ❑ 排數: 單排、雙排、三排、四排
- ❑ Pin數: 1x2~1x40 Pin、2x2~2x40 Pin、4x3~4x30 Pin
- ❑ Pin塑膠材質: PBT、NY6T、NY9T (UL 94-V0)
- ❑ 塑膠高度: 2.2、4.0、4.3、4.4、4.85、6.35mm
- ❑ Terminal: Straight、Right Angle、SMT Type
- ❑ Plating: Gold、Matte Tin、Bright Tin、Lead Tin...(The plating model and plating thickness are adjustable as the customer's request)
- ❑ Row of pin: Single row、Dual rows、Three rows、Four rows
- ❑ Positions: 1x1~1x40 Pin、2x2~2x40 Pin、3x3~3x40 Pin
- ❑ Plastic Material: PBT、NY6T、NY9T (UL 94-V0)
- ❑ Plastic height: 2.2、4.0、4.3、4.4、4.85、6.35mm

Order information

2 0 0 0 2 X 0 X X X X X X X

(1) (2) (3) (4) (5) (6) (7) (8) (9)

- (1) Pitch: 200=2.0mm
- (2) Series: 02=Female Header
- (3) Terminal: **S**=Straight Type
R=Right Angle Type / **M**=SMT Type
- (4) 0=Female
- (6) No. Of Positions: 002 to 120
- (7) Plastic Type: A, B, C,...
- (8) Row of Pin: 1=Single Row, 2=Dual Rows
3=Three Rows, 4=Four Rows
- (9) Terminal Dia. Type: 01, 02, 03...

(5)Plating Options:

Full Gold Type	Selective Plated Type(Tin=100μ")	Full Tin(Matting Tin, Bright Tin00")
G:Gold Flash	J:Gold Flash	
E:Gold 1μ"	I:Gold 1μ"	
A:Gold 3μ"	K:Gold 3μ"	
B:Gold 5μ"	L:Gold 5μ"	
C:Gold 10μ"	M:Gold 10μ"	
D:Gold 15μ"	N:Gold 15μ"	
E:Gold 30μ"	P:Gold 30μ"	

Drawing

